

Mc Mag^{3000™}

Battery Powered Electromagnetic Flow Meter



For Agriculture and Irrigation Applications

Dependable - Easy to Install - Durable





Dependable

Guaranteed 5-year battery life delivers performance season after season

Easy to Install

Saddle mount design provides hassle-free installation

Durable

Robust construction with sensor design that naturally sheds debris

Mc Mag³⁰⁰⁰ Converter



Simply opening the meter lid activates the converter display and cycles through the data screens



Mc Mag^{3000™} Flow Meter in Brief

McCrometer's award-winning Mc Mag³⁰⁰⁰ provides growers and irrigators with a new alternative for flow measurement. With a guaranteed 5-year battery life, data logging, and saddle mount design, the Mc Mag³⁰⁰⁰ delivers the dependability and ease-of-installation McCrometer has provided to the agricultural market for 60 years. The electromagnetic sensor offers accuracy as low as $\pm 1\%$ while being designed to naturally shed debris. It is available in common ag irrigation line sizes ranging from 4 to 12 inch diameter pipe and is telemetry ready for remote meter reading.

The Mc Mag³⁰⁰⁰ is suitable for agricultural water applications including:

- Irrigation
- Center Pivot Systems
- Well Monitoring
- Water Distribution
- Chemigation
- Livestock Waste Lagoons
- Surface Water
- Golf Courses and Park Management

Mc Mag³⁰⁰⁰ Specifications

• Accuracy: $\pm 2\%$ with default calibration

± 1% with custom Factory calibration

- **Battery Power**: Three 3.6V lithium-thionyl chloride D size batteries. Batteries are field replaceable. (The third battery serves as back-up power)
- Pipe Sizes: 4 12 inches (100 mm 300 mm)
- Outputs (DC powered version only): Open collector digital outputs (2) for pulse and alarm as well as
 4-20mA output
- Converter Rating: IP-67 Certified
- Data Logger: 5+ years of data. Cable sold separately

See the Mc Mag³⁰⁰⁰ Configuration Sheet for complete specifications.

www.mccrometer.com

3255 West Stetson Avenue, Hemet, CA 92545 USA Phone 800 220-2279 | 951 652-6811 | Fax 951 652-3078 Lit. No. 30121-62, Rev. 1.3 / 12-8-17

2014-2015 McCrometer, Inc. All rights reserved Printed in USA U.S. Patent 8,997,580 B2; foreign patents pending